

Safety Instructions & Regulations



1. Area of application

The rugged XCiPhone is an intrinsically safe and impact-resistant tablet PC that is designed for industrial use in potentially explosive areas classified as in accordance with directive 94/9/EC.

2. Safety precautions

These safety instructions contain information and safety regulations that must be observed to ensure safe operation under the described conditions. Failure to follow these instructions and this information can have serious consequences or constitute a violation of the applicable regulations.

Please read through these safety instructions carefully before starting to use the device! In the event of conflicting information, the safety instructions shall take precedence. In the event of any doubt, please contact Xciel.

3. Faults and damage

If there are grounds for you to believe that the safety of the device has been impaired, stop using it and remove it from the hazardous area immediately. Measures should be taken to prevent the device from being used again accidentally. The safety of the device may be impaired under the following circumstances:

- The rubber case is visibly damaged.
- The device has been exposed to excessive loads.
- The device has not been stored properly.
- The device has been damaged in transit.
- The marking or labeling on the device is illegible or non-existent.

- Malfunctions occur.
- The permitted limit values have been exceeded.

4. Safety regulations

By using the XCiPhone, it is assumed that the user has observed the generally applicable safety regulations and that he/she has read the EC Declaration of Conformity to prevent any incorrect use of the device. The following must be observed without fail:

- The iPhone should not be removed from the rubber casing.
- The iPhone should not be charged in the C1D2 area.
- Do not use the audio port (for headset) in a C1D2 area.
- It must be ensured that the device is not taken into, or used in, hazardous areas classified as C1D1 or zone 0, 1 or 20, 21, 22.

Failure to observe these safety instructions will result in expiration of the C1D2 intrinsic safety rating.

5. Ex-data

NECEX-classification: Class I, Division 2, Group A-D T5



Approved for Class I, Division 2.