



PCE Americas Inc.
711 Commerce Way
Suite 8
Jupiter
FL-33458
USA
From outside US: +1
Tel: (561) 320-9162
Fax: (561) 320-9176
info@pce-americas.com

PCE Instruments UK Ltd.
Units 12/13
Southpoint Business Park
Ensign way
Hampshire / Southampton
United Kingdom, SO31 4RF
From outside UK: +44
Tel: (0) 2380 98703 0
Fax: (0) 2380 98703 9
info@pce-instruments.com

www.pce-instruments.com/english
www.pce-instruments.com

Technical Videoscope PCE-VE 200S

PCE-VE 200-S is an industrial inspection camera, endoscope or borescope for the non-destructive evaluation (NDE) of engines, machines and more. This industrial borescope provides excellent image quality at an affordable price. An ideal tool for diagnosing issues in hard-to-reach places, the waterproof camera head features 6 LED lights with adjustable intensity for optimal illumination. In addition, digital image magnification or zoom of up to 4 times is available.

The borescope stores the recorded images and videos directly to a micro SD card memory. The 1 m / 3.28' cable length and **3.7 mm / 0.14"** diameter allow the video inspection camera unique access to view the insides of walls, pipes, vents, ducts, engines and machinery, thus eliminating the need for costly and time-consuming dismantling. Mechanical engineering, manufacturing, automotive, aviation, construction, plumbing and heating, ventilation, air conditioning and refrigeration (HVACR) professionals alike find this video inspection camera useful in a variety of applications.

Not for medical use

- Waterproof camera head (IP67 protection class)
- **3.7 mm / 0.14" diameter**
- 1 m / 3.28' cable length
- 180° image rotation
- 3.5" LCD display
- CMOS chip image sensor
- 1600 x 1200 pixels JPEG image / 640 x 480 pixels AVI video resolution
- Micro SD card memory
- Micro USB 2.0 and TV outputs

Technical contents:

Display	LCD, 3.5"
Resolution	1600 x 1200 pixels JPEG image / 640 x 480 pixels AVI video
Image rotation	180 °
Freeze functionality	Yes
Zoom	Up to 4 times digital image magnification
Menu languages	English, Spanish, French, German, Russian, Japanese, Simplified Chinese,

	Traditional Chinese
Cable diameter	3.7 mm / 0.14" cable diameter
Cable length	1 m / 3.28'
Cable rigidity	Semi-flexible (semi-rigid spiral)
Image sensor	CMOS chip
Lighting	6 white LEDs (adjustable intensity)
Field of view / angle / perspective	90 °
Sight depth	15 ... 100 mm / 0.59 ... 3.94"
Storage medium	Micro SD card
Interfaces	Micro USB 2.0, TV output (PAL), Micro SD card slot
Power supply	Rechargeable 18650 Li-ion battery
Battery capacity	2600 mAh
Battery life	Up to 5 hours from full charge
Operating conditions	Main unit and probe, in air: -10 ... +50 ° C / +14 ... +122 ° F, rel. humidity 15 ... 90% Probe, in water: +5 ... +50 ° C / +41... +122 ° F
Fluid resistance	Main unit and probe: Machine oil, light oil or 5% saline
Protection against	Main unit: Blowing rain (battery compartment must be closed), not underwater Probe: Water, oil and dust, according to protection class IP67

Delivery contents:

- 1 x PCE-VE 200-S Videoscope
- 1 x wall charger with detachable USB to Micro USB cable
- 1 x video output cable
- 1 x user manual